

Carefree Undercoat Floor Sealer

F2h

Description

A water based porous floor seal suitable for most types of porous floors prior to application of an emulsion floor polish.

Key properties

- Water based polymer emulsion
- Seals all types of porous floors including vinyl, linoleum, marble, terrazzo and other stone floors.
- Excellent adhesion to most substrates
- Semi Permanent seal for improved durability

Benefits

- Reduces the porosity of the floor and therefore improves the performance and durability of the top coats of emulsion floor polish.
- Conventional polishes can be removed without affecting the undercoat.
- Maximises protection on porous and old floors extending their life.

Use instructions

- Ensure old polish is removed
- Apply only to a clean dry floor
- Post Wet floor signs
- Using a clean mop or applicator, charge with product and tamp down in a wringer, but do not wring out the mop or applicator should be saturated but not dripping.
- Apply to the floor using overlapping figure of 8 motion. On the first coat leave a 6 inch gap along edges.
- Allow 20 – 30 minutes drying time. Ensure 1st coat is completely dry before applying a second coat. At right angles to the first coat applying product up to the edges. If required apply a 3rd coat in a similar manner.

Technical data


Appearance:	Milky emulsion
pH neat:	8.0 -9.0
pH Diluted:	Not applicable
S.G.	1.03
Viscosity	Water thin

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Store in original closed containers away from extreme temperatures.
Keep from freezing
Do not use at temperatures below 10 ° C

Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.



Carefree Undercoat

Product compatibility

Not suitable for wood floors.

Available pack sizes

2 x 5 L

Diversey Ltd

Weston Favell Centre
Northampton NN3 8PD
Tel. 0800 525 525
www.diversey.com