

WORKFORCE 12

Page: 1

Compilation date: 16/01/2014

Revision date: 30/06/2015

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WORKFORCE 12

Product code: JMS0009

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: JMS Janitorial Supplies

Unit 8. Astra Business Centre

Bonehurst Road

Salfords Surrey RH1 5TL

Tel: 01293783650 **Fax:** 01293820863

Email: sales@jmsdirect.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Dam. 1: H318

Most important adverse effects: Causes serious eye damage.

2.2. Label elements

Label elements:

Hazard statements: H318: Causes serious eye damage.

Signal words: Warning

Hazard pictograms: GHS05: Corrosion



Precautionary statements: P264: Wash hands thoroughly after handling.

P280: Wear eye protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

WORKFORCE 12

Page: 2

contact lenses, if present and easy to do. Continue rinsing.

P405: Store locked up.

P331: Do NOT induce vomiting.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM METASILICATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
229-12	6834-92-0	-	-	1-10%
BUTYL GLYCO	L			
203-905-0	111-76-2	-	-	1-10%
SODIUM HYDR	OXIDE			
215-185-5	1310-73-2	-	Skin Corr. 1A: H314	1-10%
AMINE OXIDE				
-	-	-	-	1-10%
TRISODIUM NI	TRILOTRIACETA	TE 38.5% SOLUTION		
225-768-6	5064-31-3	-	-	1-10%
BUTYL DIGLYO	COL			
203-961-6	1125-34-5	-	-	<1%
SODIUM CARE	ONATE			
207-838-8	497-19-8	-	Eye Irrit. 2: H319	<1%
QUATERNARY	AMMONIUM CO	MPOUNDS, BENZYL-C8-18-ALKYLD	IMETHYL, CHLORIDES	
264-151-6	63449-41-2	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Aquatic Acute 1: H400	<1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

WORKFORCE 12

Page: 3

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Do not attempt to take action without suitable protective clothing - see section

8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

WORKFORCE 12

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

BUTYL GLYCOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	25 ppm	50 ppm	-	-

SODIUM HYDROXIDE

UK - 2 mg/m3

AMINE OXIDE

IIK	400000	F00		
l UN	40000m	1 500	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

WORKFORCE 12

Page: 5

Solubility in water: Highly soluble

Viscosity: Non-viscous

Boiling point/range°C: 104 Flash point°C: >93

pH: >11.5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM METASILICATE

ORL RAT	LD50	1280LD50 mg/kg	
---------	------	----------------	--

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

WORKFORCE 12

Page: 6

TRISODIUM NITRILOTRIACETATE 38.5% SOLUTION

ORI	DAT	I DEO	- 2000	ml/kg
OKL	KAI	LD50	>2000	ml/kg

SODIUM CARBONATE

ORL	MUS	LD50	6600	mg/kg
ORL	RAT	LD50	4090	mg/kg
SCU	MUS	LD50	2210	mg/kg

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C8-18-ALKYLDIMETHYL, CHLORIDES

IVN	MUS	LD50	16	mg/kg
ORL	MUS	LD50	150	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

WORKFORCE 12

Page: 7

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: Not Regulated

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage. H319: Causes serious eye irritation. H400: Very toxic to aquatic life.

WORKFORCE 12

Page: 8

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.