



A005 : SELBRITE

drybright metallised polish

Description of product

Metallised polish for extreme strength and durability coupled with ease of removability. Produces a deep shine with excellent slip resistance without burnishing. Protects and prolongs the life of flooring materials. May be easily maintained by damp mopping.

Product Uses


For all linoleum, P.V.C., rubber, sealed cork, sealed wood, terrazzo and thermoplastic floors. N.B. Not suitable for use on unsealed wood, unsealed cork or laminate flooring.

Directions

Selbrite must be applied to a clean, grease free floor. Strip old polish with Selstrip then rinse thoroughly with clean water, allow the floor to dry. Apply a thin even film of Selbrite using a clean lint-free mop or applicator. Apply a second when the first coat is dry (approximately 30 mins). N.B. If the flooring is worn or porous apply Selseal prior to polish application. MAINTENANCE: Damp Mopping: As required using Lemon Floor Jell or Selden. Spray cleaning/burnishing: As required though a daily routine with Selsheen will increase the life expectancy. COVERAGE: 60 square metres per litre.

iN Insight Supported

iN Insight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>




iN Insight recommended product uses

Flooring - applying floor polish (mop application)

typical dilution
neat

Product Hazards and PPE Requirements



Risk Phrases
NC Not classified.

Safety Phrases
S2 Keep out of the reach of children., P13 Safety data sheet available for professional user on request.

Technical Data

Composition A blend of acrylic copolymers, resins and copolymer wax incorporating wetting agents and film forming aids in a stable water based emulsion form incorporating metal cross linking additives

Appearance Translucent emulsion

Colour Cream

Viscosity <10 cps

Density 1.024

pH 8.3

Activity 15%

Fragrance Characteristic slightly sweet

Stability 2 years in a unopened container

Storage Protect from freezing

Environmental Profile

Biodegradability
All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 – 2004/648/EC. This requires all surfactants to break down both quickly and completely into harmless material such as CO2 and water.

Selden Environmental Charter


- We set ourselves industry leading standards.
- Selden minimises wastage, packaging and transportation.
- If it can be recycled, it will be recycled.
- Our chemicals policy exceeds regulatory requirements.
- We don't expect other people to clean up after us.
- Conserving energy, preserving resources.
- By being innovative, we strive to do better.
- We like to work in partnership with our clients.

Visit our website for more information.

External Accreditations

- 9001 - Quality System
- 14001 - Environmental System
- 18001 - Health & Safety System
- IPPC Certified Manufacturer

Sustainability
Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages

- english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.




UKAS
accredited testing
laboratory No. 4204



SELLEN
formulating
testing
manufacturing
to
the highest
standards

Selden Research Limited

Staden Business Park, Staden Lane, Buxton Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : info@selden.co.uk | web : www.selden.co.uk

