



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name SELSPEED

Product No. F116

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Floor polish remover

1.3. Details of the supplier of the safety data sheet

Selden Research Limited t : 01298 26226 Staden Lane

Ashbourne Road f : 01298 26540
Buxton
Derbyshire e : safety@selden.co.uk

Derbyshire SK17 9RZ United Kingdom

1.4. Emergency telephone number

01298 26226

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (67/548/EEC) R42/43. C;R34. Xi;R37.

2.2. Label elements

Contains 2-AMINOETHANOL, ETHYLENEDIAMINE

Detergent Labelling: < 5% anionic surfactants

Contains BENZYL ALCOHOL

Labelling

Harmful (Xn)



Corrosive (C)

Risk Phrases R34 Causes burns., R37 Irritating to respiratory system., R42/43 May cause sensitisation by inhalation and skin

contact.

Safety Phrases S23 Do not breathe vapour/spray.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S45 In case of accident or if you feel unwell

Seek medical advice immediately (show label where possible).

S51 Use only in well-ventilated areas.

S28 After contact with skin, wash immediately with plenty of water.

S1/2 Keep locked up and out of the reach of children.

2.3. Other hazards

No other hazards known., This product does not contain any PBT or vPvB substances.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not Applicable

3.2. Mixtures

MSDS: F116 - SELSPEED language: english Page 1 of 6





2-AMINOETHANOL 10-30% CAS-No.: 141-43-5 EEC (EINECS) No. 205-483-3

Classification (EC 1272/2008) Classification (67/548/EEC)

Skin corrosion, categories 1A, 1B, 1C - H314 C:R34 Acute toxicity, category 4 - inhalation - H332 Xn:R20/21/22

Acute toxicity, category 4 - Dermal - H312 Acute toxicity, category 4 - Oral - H302

BENZYL ALCOHOL 5-10%

CAS-No.: 100-51-6 EEC (EINECS) No. 202-859-9 Classification (EC 1272/2008) Classification (67/548/EEC)

Acute toxicity, category 4 - inhalation - H332 Xn:R20/22

Acute toxicity, category 4 - Oral - H302

ETHYLENEDIAMINE 1-5% CAS-No.: 107-15-3 EEC (EINECS) No. 203-468-6

Classification (EC 1272/2008) Classification (67/548/EEC)

Xn;R21/22 Acute toxicity, category 4 - Dermal - H312 Acute toxicity, category 4 - Oral - H302 C;R34 Skin corrosion, categories 1A, 1B, 1C - H314 R10,R42/43

Flammable liquids, category 3 - H226 Respiratory sensitisation, categories 1, 1A, 1B - H334

Sodium alkylether sulphate 1-5% CAS-No.: 13150-00-0 EEC (EINECS) No.

Classification (EC 1272/2008) Classification (67/548/EEC)

Skin irritation, category 2 - H315 Xi;R38,R41

Serious eye damage, category 1 - H318

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Skin sensitisation, categories 1, 1A, 1B - H317

General information CAUTION! First Aid personnel must be aware of own risk of burns., Chemical burns must be dealt with immediately,

do not delay.

Inhalation Remove victim immediately from source of exposure., Provide rest, warmth and fresh air., If breathing stops,

provide artificial respiration., Get medical attention

Ingestion DO NOT INDUCE VOMITING!, Rinse mouth thoroughly., Drink plenty of water., Get medical attention immediately! Skin contact Immediately remove contaminated clothing., Rinse immediately with plenty of water., Continue to rinse for at least

15 minutes., Get medical attention immediately!

Promptly wash eyes with plenty of water while lifting the eye lids., Continue to rinse for at least 15 minutes and get Eye contact

medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

Ingestion Causes burns., Harmful if swallowed.

Skin contact Causes burns.

Eye contact Causes burns., Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

The product is non-combustible., Cool containers exposed to heat with water Extinguishing media

spray and remove container, if no risk is involved. Use fire-extinguishing media

appropriate for surrounding materials.

5.2. Special hazards arising from the substance or mixture

Unsuitable extinguishing media

5.3. Advice for firefighters

Special Fire Fighting

Self contained breathing apparatus and full protective clothing must be worn in case of fire. Use water to

Procedures keep fire exposed containers cool and disperse vapours.

MSDS: F116 - SELSPEED language: english Page 2 of 6







SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

For personal protection, see section 8.

6.2. Environmental precautions

Any spillage needs to be contained and not allowed to enter water courses, Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment., Absorb in vermiculite, dry sand or earth and place into containers., Collect spillage in containers, seal securely and deliver for disposal according to local regulations., Inform Authorities if large amounts are involved.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid spilling, skin and eye contact.

7.2. Conditions for safe storage, including any incompatibilities

Store separated from:, Acids.

7.3. Specific end use(s)

See product label for detailed usage and instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

 Name
 STD
 TWA - 8 Hrs
 STEL - 15 Min
 Notes

 2-AMINOETHANOL
 WEL
 1 ppm(Sk)2.5 mg/m3(Sk)
 3 ppm(Sk)7.6 mg/m3(Sk)

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Engineering measures Provide adequate general and local exhaust ventilation.

Hand protection Use protective gloves.

Eye protection Wear full-face visor or shield.

Other Protection Wear suitable protective clothing as protection against splashing or contamination.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Clear, Liquid Colour Blue.

Odour Slight odour., Solvent. Relative density 1.009 - 1.019 @ 20 °C

pH-Value, Conc. Solution 11.5 - 12.5

MSDS: F116 - SELSPEED language: english Page 3 of 6







SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Stable under normal temperature conditions.

10.2. Chemical stability

Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

None known

10.4. Conditions to avoid

Avoid contact with acids.

10.5. Incompatible materials

Strong acids., Reacts strongly with light metals such as aluminium and zinc, producing hydrogen which is Highly Flammable.

10.6. Hazardous decomposition products

When heated, toxic and corrosive vapours/gases may be formed.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological information No toxicological data is available for this mixture, however data can be provided for specific raw materials upon

request.

Inhalation May cause damage to mucous membranes in nose, throat, lungs and bronchial system.

Ingestion Causes burns., Harmful if swallowed.

Skin contact Causes burns.

Eye contact Causes burns., Risk of serious damage to eyes.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Not classed as Hazardous to the Environment but release to the environment should be avoided.

12.2. Persistence and degradability

Degradability

The surfactants contained within the product comply with the biodegradability criteria as laid down in Regulation

(EC) No 648/2004.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility: The product contains substances, which are water soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or PvB substances

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

MSDS: F116 - SELSPEED language: english Page 4 of 6





13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

 UN No. (ADR/RID/ADN)
 1760

 UN No. (IMDG)
 1760

 UN No. (ICAO)
 1760

14.2. UN proper shipping name

Proper Shipping Name: CORROSIVE LIQUID, NOS (2-AMINOETHANOL, ETHYLENEDIAMINE)

14.3. Transport hazard class(es)

ADR/RID/ADN Class 8

ADR/RID/ADN Class Class 8: Corrosive substances.

IMDG Class
ICAO Class/Division
8



Transport Labels

14.4. Packing group

ADR/RID/ADN Packing group III
IMDG Packing group III
ICAO Packing group III

14.5. Environmental hazards

Environmentally Hazardous substance/Marine Pollutant No.

14.6. Special precautions for user

Tunnel Restriction Code E

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not relevant

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UK Regulatory References Environmental Listing The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Rivers (Prevention of Pollution) Act 1961., Control of Pollution (Special Waste Regulations) Act 1980.

Statutory Instruments

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716)., Control of

Substances Hazardous to Health.

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40., CHIP for everyone HSG(108).

System of specific information relating to Dangerous Preparations. 2001/58/EC., Dangerous Preparations Directive 1999/45/EC., Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a

EU Legislation

European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments., Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006 with amendments.

National Regulations The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007).

MSDS: F116 - SELSPEED language: english Page 5 of 6





15.2. Chemical Safety Assessment

No chemical assessment has been carried out as this Safety Data Sheet is for a mixture

SECTION 16: OTHER INFORMATION

General information

The following risk phrases relate to the raw materials in the product and not the product itself:-

Revision Comments

Safety Data Sheet revised to be in accordance with EU Regulation No 453/2010 - REACH Regulations.

Revision Date 30/01/2013

Revision 5

Risk Phrases In Full R20/21/22 Harmful by inhalation, in contact with skin and if swallowed., R34 Causes burns., R37 Irritating to

respiratory system. | R20/22 Harmful by inhalation and if swallowed. | R38 Irritating to skin., R41 Risk of serious damage to eyes. | R10 Flammable., R34 Causes burns., R21/22 Harmful in contact with skin and if swallowed.,

R42/43 May cause sensitisation by inhalation and skin contact.|

Hazard Statements In Full H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

MSDS: F116 - SELSPEED language: english Page 6 of 6