

F116 : SELSPEED

rinse free polish stripper

Description of product

Rinse Free Polish Stripper Latest advanced technology to unlock metallised polish. Advanced soil suspending formula helps recovery. Low foam for speed use and ultimate wet pickup.

Product Uses

Selspeed is a modern alternative to traditional caustic based polish strippers. Use Selspeed in well ventilated areas. Whilst it is good practice to rinse the floor with a mild acidic water solution before re-polishing this is not necessary with Selspeed.

Directions

Mop Stripping: Dilute Selspeed 1:5 with water. Mop the floor liberally. Leave for 5-10 minutes. Using the mop agitate with a fresh solution and leave for a further 5 minutes. Remove slurry with a mop or wet pickup. **Scrubbing machine:** Dilute Selspeed 1:10 with water. Mop the floor liberally. Leave for 5-10 minutes and then scrub with a slow machine fitted with a black pad. Remove slurry with a mop or wet pickup. **Spray Stripping:** Dilute Selspeed 1:20 with water. Spray lightly ahead of machine fitted with a suitable pad at medium speed. N.B. Do not use 'Selspeed' to remove emulsion polish from sealed wooden floors, Selsate is recommended. Do not use 'Selspeed' on linoleum, unsealed wood or unsealed cork floors.

iNsight Supported

iNsight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>



typical dilution

iNsight recommended product uses

Flooring - floor stripping / polish removal (machine)	1 : 10
Flooring - floor stripping / polish removal (mop)	1 : 5
Flooring - floor stripping / polish removal (spray)	1 : 20

Product Hazards and PPE Requirements



HARMFUL



CORROSIVE



Risk Phrases

R34 Causes burns., R37 Irritating to respiratory system., R42/43 May cause sensitisation by inhalation and skin contact.

Safety Phrases

S23 Do not breathe vapour/spray., S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice., S36/37/39 Wear suitable protective clothing, gloves and eye/face protection., S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible)., S51 Use only in well-ventilated areas., S28 After contact with skin, wash immediately with plenty of water., S1/2 Keep locked up and out of the reach of children.

Technical Data

Composition	An aqueous blend of Alkaline builders, sequestering agents, soil suspending agents and detergents
Appearance	Clear thin liquid
Colour	Blue
Cloud Point	>60
Density	1.014
pH	>13.5
Fragrance	slight solvent
Stability	2 years in a unopened container
Storage	Protect from freezing

Environmental Profile

Biodegradability

All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 – 2004/648/EC. This requires all surfactants to break down both quickly and completely into harmless material such as CO2 and water.

Selden Environmental Charter

- We set ourselves industry-leading standards.
 - Selden minimises wastage, packaging and transportation.
 - If it can be recycled, it will be recycled.
 - Our chemicals policy exceeds regulatory requirements.
 - We don't expect other people to clean up after us.
 - Conserving energy, preserving resources.
 - By being innovative, we strive to do better.
 - We like to work in partnership with our clients.
- Visit our website for more information.

External Accreditations

9001 - Quality System
14001 - Environmental System
18001 - Health & Safety System
IPPC Certified Manufacturer

Sustainability

Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages



english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.



ISO 9001



ISO 14001



ISO 18001

UKAS

accredited testing
laboratory No. 4204



SELDEN
formulating
testing
manufacturing
to
the highest
standards

Selden Research Limited

Staden Business Park, Staden Lane, Buxton
Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : info@selden.co.uk | web : www.selden.co.uk

