

Temp-Proof 333

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile
- **Length (inches)** 12.5
- **Thickness (inches)** Heavy Wt.
- **Colour/Color** Black
- **Interior finish** Knitted thermal protection
- **Size / EAN** 9
- **Packaging** 1 pair/bag - 6 pairs/bag - 12 pairs/carton



PERFORMANCE RESULTS

Certification category 2



12X



X2XXXX



2332

Legends



**MECHANICAL
HAZARDS
EN 388**

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4
 └─ Puncture resistance
 └─ Tear resistance
 └─ Blade cut resistance
 └─ Abrasion resistance



**LOW CHEMICAL
PROTECTION
EN 374**



**MICRO-ORGANISMS
EN 374**



**RADIOACTIVE
CONTAMINATION
EN 421**



**HEAT
AND FIRE
EN 407**

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4
 └─ Resistance to large quantities of molten metal
 └─ Resistance to small drops of molten metal
 └─ Radiant heat resistant
 └─ Convective heat resistance
 └─ Contact heat resistance
 └─ Burning behaviour



**SPECIFIC CHEMICAL
PROTECTION
EN 374**

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS
EN 511**

PERFORMANCE LEVELS

0-4 0-4 0 or 1
 └─ Water permeability
 └─ Contact cold resistance
 └─ Convective cold resistance

For more details: www.mapa-pro.com

MAPA
PROFESSIONAL
www.mapa-pro.com

Temp-Proof 333

DESCRIPTION AND GENERAL PROPERTIES

- Excellent thermal insulation in wet, oily or steamy conditions
- Good resistance to oils, greases and hydrocarbons

MAIN FIELDS OF USE

Other industries

- [Boiler room work](#)
- Handling of hot steel after welding
- Heat treatment up to 250°C (autoclaves, etc.)
- Steam cleaning
- Steel quenching

Rubber industry

- [Vulcanization, demoulding, forming, etc.](#)

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- Put the gloves on dry, clean hands.
- Ensure the inside of the gloves is dry before putting them on again.
- In case of sustained use, alternate 2 pairs.
- Inspect the gloves for cracks or snags before reusing them.
- It is not recommended for persons sensitized to dithiocarbamates or thiazoles to use these gloves, nor to use them next to moving machinery.

Laundrying conditions

Caution : improper use of the gloves or submitting them to a cleaning or laundrying process that is not specifically recommended can alter their performance levels.

LEGISLATION

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.

This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0075/014/162/05/07/0158

- Issued by the notified body nr

0075

C.T.C. – rue H. FRENKEL - F-69367 LYON CEDEX 07